

## **Sheathed Screen Thermometer: Ordinary**

Sheathed screen ordinary thermometer to BS692 for use in a Stevenson's screen.

Ordinary 1/C	
Range	-25°C to 55°C
<b>Scale Division</b>	0.5°C
Dimensions	325mm x 13mm diameter
Accuracy	-0.2/+0.05°C
Weight	65 grams
<b>Mercury Content</b>	10 grams

## **Sheathed Screen Thermometer: Maximum**

Sheathed screen maximum thermometer to BS692 for use in a Stevenson's screen.

Maximum 2/C	
Range	-20°C to 55°C
<b>Scale Division</b>	0.5°C
Dimensions	340mm x 13 mm diameter
Accuracy	-0.2/+0.05°C
Weight	70 grams
Mercury Content	10 grams

## **Sheathed Screen Thermometer: Minimum**

Sheathed screen minimum thermometer to BS692 for use in a Stevenson's screen spirit filled.

Minimum 2/C	
Range	-35°C to 40°C
<b>Scale Division</b>	0.5℃
Dimensions	340mm x 13mm diameter
Accuracy	+/-0.2°C
Weight	65 grams

<sup>\*</sup>This can be used as a "Grass Minimum" by using a small pair of yokes to hold the thermometer at grass level.

Calibration certificates traceable to UKAS will be provided.